April 28, 2003

Andrew Fanara EPA Program Manager ENERGY STAR for Exit Signs United States EPA 1200 Pennsylvania Ave., NW MC 6202J Washington, DC 20460

Subject: ENERGY STAR Program Requirements for Exit Signs Draft 2-Eligibility Criteria – Version 3.0

Dear Mr. Fanara:

It is my understanding that you are allowing comments to documents that have been posted on the Energy Star website. We would like to take this opportunity to comment on two of the comments submitted by Manny Muniz Associates, LLC regarding the comments submitted by Lithonia.

## Minimum Luminance Requirements

The previous version of Energy Star Program Requirements for Exit Signs specified a minimum luminance of 8.6 cd/m<sup>2</sup>. The subject version has dropped this minimum luminance requirement, and simply requires the sign to comply with UL 924. We are objecting to EPA dropping the 8.6 cd/m<sup>2</sup>. We do not attempt to interpret UL 924 because that is best left to UL.

## Observer Requirements

The mention of 24/40 visual acuity is clearly a typographical error that slipped though. There was no attempt to dispute the fact that 20/40 is published in UL 924, Sec. 40.1.2(a). However, the adequacy of this requirement is being questioned.

Sincerely,

Billy G. Helton Manager, Engineering Services

h:\esg\bgh01\Energy Star Draft 2 Version 3.0 4-28-03.doc